

ADV 1000



General: Classic low profile luminaire
Body: Aluminium
 Diameter 430mm, Depth 115mm surface or 67mm recessed
 100mm void depth required for recessing
Diffuser: UV resistant, flame retardant, injection moulded opal or vac formed prismatic polycarbonate, push fit
Finishes: Gloss white (RAL 9003) polyester powder coat, polished silver anodise, brushed silver anodise, polished gold anodise
Fixing: Wall or ceiling mounting, rear central cable entry, besa fixing, screw fixing, recessing option
Control Gear: HF ballast. Dimmable options available on request
Emergency: Integral control gear, 3 hour maintained operation. Self test versions available on request

Lamp	Operation	Diffuser	Fixing	White Gloss	Polished Silver	Brushed Silver	Polished Gold
28W 2D	Mains	Opal	Surface	1000-001	1000-002	1000-003	1000-004
28W 2D	Mains	Opal	Recessed	1000-005	1000-006	1000-007	1000-008
28W 2D	Emergency	Opal	Surface	1000-009	1000-010	1000-011	1000-012
28W 2D	Emergency	Opal	Recessed	1000-013	1000-014	1000-015	1000-016
28W 2D	Mains	Prismatic	Surface	1000-081	1000-082	1000-083	1000-084
28W 2D	Mains	Prismatic	Recessed	1000-085	1000-086	1000-087	1000-088
28W 2D	Emergency	Prismatic	Surface	1000-089	1000-090	1000-091	1000-092
28W 2D	Emergency	Prismatic	Recessed	1000-093	1000-094	1000-095	1000-096
38W 2D	Mains	Opal	Surface	1000-017	1000-018	1000-019	1000-020
38W 2D	Mains	Opal	Recessed	1000-021	1000-022	1000-023	1000-024
38W 2D	Emergency	Opal	Surface	1000-025	1000-026	1000-027	1000-028
38W 2D	Emergency	Opal	Recessed	1000-029	1000-030	1000-031	1000-032
38W 2D	Mains	Prismatic	Surface	1000-097	1000-098	1000-099	1000-100
38W 2D	Mains	Prismatic	Recessed	1000-101	1000-102	1000-103	1000-104
38W 2D	Emergency	Prismatic	Surface	1000-105	1000-106	1000-107	1000-108
38W 2D	Emergency	Prismatic	Recessed	1000-109	1000-110	1000-111	1000-112
55W T-R16	Mains	Opal	Surface	1000-145	1000-146	1000-147	1000-148
55W T-R16	Mains	Opal	Recessed	1000-149	1000-150	1000-151	1000-152
55W T-R16	Mains	Prismatic	Surface	1000-153	1000-154	1000-155	1000-156
55W T-R16	Mains	Prismatic	Recessed	1000-157	1000-158	1000-159	1000-160