



ADV 1400



General: IP 65 protection
Body: Die-cast aluminium housing
 Diameter 360mm
 Plain depth 145mm, Cross depth 220mm
 Hood and Grill depth 170mm
Diffuser: UV resistant, flame retardant, injection moulded, opal polycarbonate
Finishes: Black, white or silver
Fixing: Wall or ceiling mounting, screw fixing
Control Gear: HF ballast. LED options available on request.
Emergency: Integral control gear, 3 hour maintained operation. Self test versions available on request

Lamp	Operation	Style	Black	White	Silver
28W 2D	Mains	Plain	1400-001	1400-025	1400-013
28W 2D	Emergency	Plain	1400-002	1400-026	1400-014
28W 2D	Mains	Cross	1400-003	1400-027	1400-015
28W 2D	Emergency	Cross	1400-004	1400-028	1400-016
28W 2D	Mains	Grill	1400-047	1400-055	1400-063
28W 2D	Emergency	Grill	1400-048	1400-056	1400-064
38W 2D	Mains	Plain	1400-005	1400-029	1400-017
38W 2D	Emergency	Plain	1400-006	1400-030	1400-018
38W 2D	Mains	Cross	1400-007	1400-031	1400-019
38W 2D	Emergency	Cross	1400-008	1400-032	1400-020
38W 2D	Mains	Grill	1400-049	1400-057	1400-065
38W 2D	Emergency	Grill	1400-050	1400-058	1400-066
26W TC-D	Mains	Hood	1400-037	1400-039	1400-041
26W TC-D	Emergency	Hood	1400-038	1400-040	1400-042