

ADV 2600



General: Straight edge circular compact
Body: Mild steel
 Diameter 363mm, 463mm or 563mm, Depth 105mm
Diffuser: UV resistant, flame retardant, injection moulded opal or vac formed prismatic polycarbonate, push fit
 Anti vandal diffuser fixing available on request
Finishes: Gloss white (RAL 9003) polyester powder coat, polished chrome, satin nickel, polished gold
Fixing: Wall or ceiling mounting, screw fixing
Control Gear: HF ballast. LED and dimmable options available on request
Emergency: Integral control gear, 3 hour maintained operation. Self test versions available on request
Night Light: Please contact Sales for details

Lamp	Operation	Diffuser	Diameter	White Gloss	Polished Chrome	Satin Nickel	Polished Gold
28W 2D	Mains	Opal	363mm	2600-501	2600-502	2600-503	2600-504
28W 2D	Mains	Prismatic	363mm	2600-505	2600-506	2600-507	2600-508
38W 2D	Mains	Opal	463mm	2600-009	2600-010	2600-011	2600-012
38W 2D	Emergency	Opal	463mm	2600-013	2600-014	2600-015	2600-016
38W 2D	Mains	Prismatic	463mm	2600-041	2600-042	2600-043	2600-044
38W 2D	Emergency	Prismatic	463mm	2600-045	2600-046	2600-047	2600-048
2*24W TC-L	Mains	Opal	463mm	2600-025	2600-026	2600-027	2600-028
2*24W TC-L	Emergency	Opal	463mm	2600-029	2600-030	2600-031	2600-032
2*24W TC-L	Mains	Prismatic	463mm	2600-057	2600-058	2600-059	2600-060
2*24W TC-L	Emergency	Prismatic	463mm	2600-061	2600-062	2600-063	2600-064
3*24W TC-L	Mains	Opal	463mm	2600-065	2600-066	2600-067	2600-068
3*24W TC-L	Mains	Prismatic	463mm	2600-069	2600-070	2600-071	2600-072
55W 2D	Mains	Opal	463mm	2600-073	2600-074	2600-075	2600-076
55W 2D	Mains	Prismatic	463mm	2600-077	2600-078	2600-079	2600-080
55W 2D	Mains	Opal	563mm	2600-601	2600-602	2600-603	2600-604
55W 2D	Emergency	Opal	563mm	2600-605	2600-606	2600-607	2600-608
3*24W TC-L	Mains	Opal	563mm	2600-609	2600-610	2600-611	2600-612
3*24W TC-L	Emergency	Opal	563mm	2600-613	2600-614	2600-615	2600-616
4*24W TC-L	Mains	Opal	563mm	2600-617	2600-618	2600-619	2600-620