

ADV 3500

ADV Lighting Ltd



- General:** Side light to avoid shadowing
Body: Mild steel
 Diameters 359mm or 459mm, Depth 135mm
Diffuser: UV resistant, flame retardant, injection moulded opal or vac formed prismatic polycarbonate, push fit
 Side diffuser opal
 Anti vandal diffuser fixing available on request
Finishes: Gloss white (RAL 9003) polyester powder coat, polished chrome, satin nickel, polished gold
Fixing: Wall or ceiling mounting, screw fixing
Control Gear: HF ballast. Dimmable options available on request
Emergency: Integral control gear, 3 hour maintained operation. Self test versions available on request

Lamp	Operation	Diffuser	Diameter	White Gloss	Polished Chrome	Satin Nickel	Polished Gold
28W 2D	Mains	Opal	359mm	3500-501	3500-502	3500-503	3500-504
28W 2D	Emergency	Opal	359mm	3500-505	3500-506	3500-507	3500-508
28W 2D	Mains	Prismatic	359mm	3500-509	3500-510	3500-511	3500-512
28W 2D	Emergency	Prismatic	359mm	3500-513	3500-514	3500-515	3500-516
38W 2D	Mains	Opal	359mm	3500-517	3500-518	3500-519	3500-520
38W 2D	Emergency	Opal	359mm	3500-521	3500-522	3500-523	3500-524
38W 2D	Mains	Prismatic	359mm	3500-525	3500-526	3500-527	3500-528
38W 2D	Emergency	Prismatic	359mm	3500-529	3500-530	3500-531	3500-532
55W 2D	Mains	Opal	459mm	3500-001	3500-002	3500-003	3500-004
55W 2D	Emergency	Opal	459mm	3500-005	3500-006	3500-007	3500-008
55W 2D	Mains	Prismatic	459mm	3500-009	3500-010	3500-011	3500-012
55W 2D	Emergency	Prismatic	459mm	3500-013	3500-014	3500-015	3500-016
22W + 40W T-R16	Mains	Opal	459mm	3500-017	3500-018	3500-019	3500-020
22W + 40W T-R16	Emergency	Opal	459mm	3500-021	3500-022	3500-023	3500-024
22W + 40W T-R16	Mains	Prismatic	459mm	3500-025	3500-026	3500-027	3500-028
22W + 40W T-R16	Emergency	Prismatic	459mm	3500-029	3500-030	3500-031	3500-032