

ADV 3600

ADV Lighting Ltd



General: Side light to avoid shadowing
Body: Mild steel, Diameters 540mm, Depth 105mm
Diffuser: UV resistant, flame retardant, injection moulded opal or vac formed prismatic polycarbonate
 Side diffuser opal
 Anti vandal diffuser fixing available on request
Finishes: Gloss white (RAL 9003) polyester powder coat, polished chrome, satin nickel, polished gold
Fixing: Wall or ceiling mounting, screw fixing
Control Gear: HF ballast. Dimmable options available on request
Emergency: Integral control gear, 3 hour maintained operation. Self test versions available on request
Corridor: Indicates TRIDONIC.ATCO corridorFUNCTION with integral PIR (Only compatible with ceiling installation)

Lamp	Operation	Diffuser	White Gloss	Polished Chrome	Satin Nickel	Polished Gold
55W 2D	Mains	Opal	3600-001	3600-002	3600-003	3600-004
55W 2D	Emergency	Opal	3600-005	3600-006	3600-007	3600-008
55W 2D	Mains	Prismatic	3600-009	3600-010	3600-011	3600-012
55W 2D	Emergency	Prismatic	3600-013	3600-014	3600-015	3600-016
3*24W TC-L	Mains	Opal	3600-017	3600-018	3600-019	3600-020
3*24W TC-L	Emergency	Opal	3600-021	3600-022	3600-023	3600-024
3*24W TC-L	Mains	Prismatic	3600-025	3600-026	3600-027	3600-028
3*24W TC-L	Emergency	Prismatic	3600-029	3600-030	3600-031	3600-032
2*24W TC-L	Mains + Corridor	Opal	3600-801	3600-802	3600-803	3600-804
2*24W TC-L	Emergency + Corridor	Opal	3600-805	3600-806	3600-807	3600-808
2*24W TC-L	Mains + Corridor	Prismatic	3600-809	3600-810	3600-811	3600-812
2*24W TC-L	Emergency + Corridor	Prismatic	3600-813	3600-814	3600-815	3600-816