

# ADV 4000



- General:** Decorative compact with sloping flange  
**Body:** Mild steel  
Diameters 500mm or 600mm, Depth 105mm  
**Diffuser:** UV resistant, flame retardant, injection moulded opal or vac formed prismatic polycarbonate, push fit  
Anti vandal diffuser fixing available on request  
**Finishes:** Gloss white (RAL 9003) polyester powder coat, polished chrome, satin nickel, polished gold  
**Fixing:** Wall or ceiling mounting, screw fixing  
**Control Gear:** HF ballast. LED and dimmable options available on request  
**Emergency:** Integral control gear, 3 hour maintained operation. Self test versions available on request  
**Night Light:** Please contact Sales for details

Lamp	Operation	Diffuser	Diameter	White Gloss	Polished Chrome	Satin Nickel	Polished Gold
28W 2D	Mains	Opal	500mm	4000-501	4000-502	4000-503	4000-504
28W 2D	Mains	Prismatic	500mm	4000-505	4000-506	4000-507	4000-508
38W 2D	Mains	Opal	500mm	4000-509	4000-510	4000-511	4000-512
38W 2D	Mains	Prismatic	500mm	4000-513	4000-514	4000-515	4000-516
55W 2D	Mains	Opal	600mm	4000-001	4000-002	4000-003	4000-004
55W 2D	Emergency	Opal	600mm	4000-005	4000-006	4000-007	4000-008
55W 2D	Mains	Prismatic	600mm	4000-009	4000-010	4000-011	4000-012
55W 2D	Emergency	Prismatic	600mm	4000-013	4000-014	4000-015	4000-016
3*24W TC-L	Mains	Opal	600mm	4000-017	4000-018	4000-019	4000-020
3*24W TC-L	Emergency	Opal	600mm	4000-021	4000-022	4000-023	4000-024
3*24W TC-L	Mains	Prismatic	600mm	4000-025	4000-026	4000-027	4000-028
3*24W TC-L	Emergency	Prismatic	600mm	4000-029	4000-030	4000-031	4000-032